

SUBAL CD5

for Canon EOS 5D



The housing incorporates an excellent viewfinder optic for full frame viewing. Optionally the housing can be assembled with the new magnifying **Viewfinder Optic GS 180**.

As with all our products choice of materials, machining, surface protection and finish conform with SUBAL's well known standards of reliability and workmanship.

All SUBAL ports with bayonet mount are fitting this housing.

Controls/Functions:

Power On/OFF, Shutter Release, Front and Rear Main Dial, Manual Focus/Zoom, Mode Dial, Lens Release, AE-Lock.

Push Buttons for: Light, AF/WB Selector, Drive-ISO, Metering System/Flash Power Compensation, Menu, Info, Jump, Playback, Delete, Focus Area Selector, Set.

Technical Data:

Seawater resistant aluminium alloy, machined from block, extreme surface hardening and corrosion resistance through HardCoating. All parts manufactured from anodized and hard coated aluminium, acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings.

O-rings in hard coated glands.

SUBAL QuickLock latching system.



Configuration:

- **W x H x D** Approx. 240x 175x 140 mm (w/o port and handles, with standard view finder)
- **Weight** Approx. 2,2 kg (w/o port and accessories)
- **Buoyancy** All but neutral (depended on used port and accessories)
- **2 Flash connectors** Optionally Nikonos V, IKELITE or subtronic S6 sockets.
- **Strobe arm mounts** Two 25 mm T-plates, TLC- or Ultralight base optional
- **Max. Depth rating** 70 m (210 ft)