

SUBAL ND70

for Nikon D70

The **SUBAL ND70** housing for the digital SLR camera Nikon D70 consequently follows the very successful and supremely approved design strategy of the new generation of underwater housings. The ergonomic placement of all the important controls provides comfortable handling of the camera functions. The camera is mounted on a saddle which provides precise positioning inside the housing, mounting failures are nearly impossible. A 4 mm main O-ring and the SUBAL QuickLock latching system provide maximum security.

Threaded holes on the base and in the top-accessory shoe allow mounting of trays or aiming lights etc.

Generous shading of the LCD-monitor provides a bright and clear image. The housing incorporates an excellent viewfinder optic for full frame viewing. Optionally the housing can be assembled with the new magnifying **Viewfinder Optic GS 180**. As with all our products choice of materials, machining, surface protection and finish conform with SUBAL's well known standards of reliability and workmanship.

All SUBAL ports with bayonet mount are fitting this housing.



Controls/Functions:

Shutter Release, Power On/Off, Manual Focus/Zoom, Front and Rear Main Dial, Program Dial, Focus Area Selector, AF/AE Lock, Lens Release.

Push buttons for: Display Light, Exposure Compensation, Flash Exposure Compensation, Metering System, Multi Selector, Menu, Monitor/Play, Thumbnail View, White Balance, Quality, Protect, Delete, Enter, Bracketing.

Technical Data:

Seawater resistant aluminium alloy, machined from block, extreme surface hardening and corrosion resistance through HardCoating. All parts manufactured from anodized and hard coated aluminium, acid proof stainless steel or high quality plastics. Seals are seamless precision O-rings. SUBAL QuickLock latching system.



Configuration:

- **W x H x D** Approx. 230 x 162 x 150 mm (w/o port and handles)
- **Weight** approx. 1,8 kg (w/o port and accessories)
- **Buoyancy** Nearly neutral (depended on used port and accessories)
- **Flash connector** 1 Nikonos V TTL socket (Standard). Other systems available
- **Flash arm mounts** 1 T-plate 25 mm, TLC- or Ultralight base optional
- **Max. Depth rating** 70 m (210 ft.)



SUBAL